



KRAMER

VM-4H2

Distributeur amplificateur HDMI 2.0 4K60
4:4:4 1x4

| HDMI | HDCP Compliant | 4K/60 UHD (4:4:4)
| 4K HDR



Le VM-4H2 est un distributeur amplificateur pour signaux 4K@60Hz (4:4:4) HDCP 2.2 HDMI 2.0. Il égalise et reclocke le signal à partir d'une entrée HDMI et le distribue vers quatre sorties identiques

FEATURES

Max. Data Rate - 17.82Gbps (5.94Gbps per graphic channel)

Max. Resolution - 4K@60Hz (4:4:4)

HDMI Signal Transmission - HDR, HDMI 2.0 and HDCP 2.2 compliant signal, supporting deep color, x.v.Color™, lip sync, 7.1 PCM, Dolby TrueHD, DTS-HD, CEC (OUT 1 only), 2K, 4K, and 3D

Intelligent EDID Handling - Use connected display EDID or default EDID, with EDID lock and RGB-force options, to ensure proper operation of HDMI source and display systems

Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances

Force RGB - When the display lacks YCbCr capabilities, the user can force native delivery of the RGB color format in HDMI content to improve picture quality

Selectable HDCP Authorization - Allows the user to control the appearance of an HDCP or non-HDCP input to the source to permit delivery of protection-free content, such as personal clips and charts, without HDCP encryption. HDCP protected content is not passed in non-HDCP mode

Field Maintenance - RS-232 connection for simple field firmware upgrade, status indicators for HDMI input and output connected signals, and power indicator, for ease of maintenance and troubleshooting

Easy Installation - Compact Mega TOOLS™ fan-less enclosure for over-ceiling mounting, or side-by-side rack mounting



KRAMER

TECHNICAL SPECIFICATIONS

ENTREE:	1 connecteur HDMI
SORTIES:	4 connecteurs HDMI PORT: 1 RS-232 pour mise à jour firmware
DEBIT DE DONNEES MAX:	17.82Gbps (5.94Gbps par canal graphique) supportant des résolutions jusqu'à 4K @60Hz (4.4.4)
COMPATIBILITE AVEC LE STANDARD HDMI:	Support HDMI 2.0 et HDCP 2.2
LEDS INDICATRICES:	ON, IN, OUT 1 vers 2
TEMPERATURE D'UTILISATION:	0° à +40°C
TEMPERATURE DE STOCKAGE:	-40° à +70°C
HUMIDITE:	10% à 90%
CONSOMMATION:	5V DC, 730mA
ACCESSOIRES INCLUS:	Alimentation
PRODUCT DIMENSION:	18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00") W, D, H
PRODUCT WEIGHT:	0.4kg (0.9lbs) approx
SHIPPING DIMENSION:	34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H
SHIPPING WEIGHT:	1.0kg (2.1lbs) approx

